



” The exclusive
POS System

- Robust checkout system with resistive or PCAP touch monitor and stand
- Without fan: silent and reliable (P2100)
- Hospitality professional with IP64-protected front panel
- Efficient Intel processors at up to 2.5 GHz, and up to 8 GB RAM

Specifications – P2100/2300

		P2100	P2300
System	CPU	Intel Celeron J1900, Quad-Core, 2.0 GHz (fanless)	Intel Celeron G540 2.5 GHz
	System memory	4 GB DDR3 RAM (up to 8 GB)	4 GB DDR3 RAM
	Chipset	BayTrail Plattform	Intel H61
	Compact Flash	CompactFlash card support	CFast-Card support
	Hard disk drive	320 GB HDD, optional SSD	
	Audio	On-board	
	Housing	Aluminium	
	Supported operating systems	Linux, Windows Embedded Standard 7, Windows Embedded Standard 8, Windows POSReady 7, Windows POSReady 8	
Display	Graphics chip	Intel HD Graphics	Intel integrated
	LCD screen size	38.1cm (15")	
	Maximum resolution	1,024 x768 pixels	
	Brightness	350 cd/m ²	250 cd/m ²
	Touch screen	5-wire resistive, projected capacitive (optional)	
Interfaces	USB 2.0	4x	
	Serial/COM	3x DB9, 1x RJ45	2x DB9, 1x RJ45
	Parallel	Available on demand	
	LAN	1 x RJ45 10/100/1000 Base-T	
	VGA	1x	
	PS/2	1x	
	Cash drawer port	1x RJ11 (12V)	
	Audio	Line-out, mic-in, speaker	
PSU	Power adapter	90 watts	180 watts
Other	Dimensions (WxHxD)	323,6 x 264,2 x 368 mm	
	Weight	7.6 kg	
	Operating temperature	0 to 40 °C	
	Certification	CE, FCC, RoHS, IP64-Front	
	Mount	VESA 100 mm	
Options	Magnetic stripe reader	Choice of MSR (track 1, 2, 3), MSR + iButton reader, MSR + smart card reader + iButton reader, MSR + smart card reader + fingerprint reader	
	Customer display	VFD, 2 x 20 characters	
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") screen size	
	Barcode scanner	1D or 2D barcode scanner (optional RFID capability)	
	Waiter lock	iButton (optional RFID capability)	
	RFID	13.56 MHz (MIFARE)	
	Farbvariante	black, white	
	USV	up to 1 hour battery back-up	

Your Dealer